

Thermo Scientific Finnpiquette Novus Multichannel Electronic Pipettors

Finnpiquette Novus Multichannel Pipettors offer superior performance for microplate applications.

Finnpiquette Novus pipettors deliver outstanding performance with greater ease of use and less risk of injury. Unique to Novus pipettors, the adjustable index-finger trigger action prevents common repetitive stress injuries caused by thumb-driven pipettes, and the easy-to-follow prompts guide users through 10 pipetting functions.

Repetitive dispensing with stepper functionality excels at filling microplates by saving time and effort compared to manual pipettors. Dispensing of two selected volumes with an air cap between, followed by a mix step with DILUTE+MIX function, is excellent for the preparation of standard curves. The Novus 1200 µL 8-channel pipette is ideal for high volume stepping of an entire plate, (e.g., dispense 100 µL up to 12 columns). The pipettor is also a practical tool for filling high volume deep well plates. For 384-microplate applications, choose the Novus 16-channel model.

Details

- **Intuitive user interface** features a simple button layout and no abbreviations
- **Seven languages:** Operate in the user's native language (English, French, German, Italian, Japanese, Spanish, Swedish)
- **Backlit technology** eliminates surrounding light reflections and improves contrast in low-light conditions
- **10 pipetting functions and nine aspirate/dispense speeds:** Ultimate in flexibility and variety not available in manual pipettes
- **Personalize up to nine programs** for your most common protocols: Save time and ensure accurate and precise pipetting
- **Easy in-lab, 2- or 1-point calibration:** For accurate and precise results in different applications
- **Fully autoclavable tip cones***:** Prevents cross-contamination
- **Long-life lithium-ion battery** allows approximately 4,000 pipetting operations; recharges in approximately one hour
- **A large volume range from 1 µL up 1200 µL:** Accommodates many applications

Ergonomic Design

- **Natural index finger pipetting operation:** Lets the thumb relax while pipetting
- **Adjustable finger rest:** For balance and comfort
- **Soft-touch tip ejection:** Minimizes thumb strain
- **Extremely lightweight construction:** Work longer without fatigue



Ordering Information: Ideal for use with Thermo Scientific Finnpiquette pipette tips, as specified in the ordering table. Also compatible with most universal-fit tips.

Includes: Finnpiquette Novus, universal charger, service tool, instruction manual and calibration certificate

Warranty: Two years with Web registration

Cat. No.	Channels	Range (calibration)	Range (functional**)	Increment	Accuracy %*	Precision %*	Color code	Compatible FinnTip
46300000	8	1-10 µL	0.5-10 µL	0.1 µL	±12.0 to ±2.4	8.0 to 1.6	Pink	Flex 10, 10, 20 micro, 50 micro
46300100	12	1-10 µL	0.5-10 µL	0.1 µL	±12.0 to ±2.4	8.0 to 1.6	Pink	Flex 10, 10, 20 micro, 50 micro
46300200	8	5-50 µL	2.5-50 µL	0.1 µL	±5.0 to ±1.5	2.0 to 0.7	Yellow	Flex 200, 200 Ext, 250
46300300	12	5-50 µL	2.5-50 µL	0.1 µL	±5.0 to ±1.5	2.0 to 0.7	Yellow	Flex 200, 200 Ext, 250
46300700	16	5-50 µL	2.5-50 µL	0.1 µL	±5.0 to ±1.5	2.0 to 0.7	Turquoise	50
46300400	8	30-300 µL	15-300 µL	1 µL	±5.0 to ±1.0	2.0 to 0.3	Orange	Flex 300, 300
46300500	12	30-300 µL	15-300 µL	1 µL	±5.0 to ±1.0	2.0 to 0.3	Orange	Flex 300, 300
46300800	8	100-1200 µL	50-1200 µL	1 µL	±3.0 to ±1.0	0.9 to 0.2	Turquoise	Flex 1200

*Factory calibration limits achieved under strictly controlled conditions (ISO 8655). **The Functional volume range indicates the volume range that the pipette can cover in the Stepper, Sequential Stepper and Sequential Aspirate functions. ***Except the 8-channel 1200 µL model