


COMPACT CENTRIFUGE Z 206A



Rotor/Bucket






Angle rotor 12 x 15 ml
Angle: 32°



Order No.: 221.54 V01

Adapters

max. speed: 6000 rpm
RCF-value: 4427 xg
max. radius: 11,0 cm
Acceleration time in s: 33 / 95
Deceleration time in s: 51 / 257

15 ml Falcon	15 ml	7 ml	5 ml	1,5 / 2,0 ml
				
17 without	17 without	13 701.011	13 701.012	11 701.015
Length in mm	105-120	100	65-75	42
Adapter Order No.:				







Angle rotor 6 x 50 ml
Angle: 40°




Order No.: 221.55 V01

Ø Tubes in mm
Length in mm
Adapter Order No.:

max. speed: 6000 rpm
RCF-value: 4427 xg
max. radius: 11,0 cm
Acceleration time in s: 41 / 91
Deceleration time in s: 52 / 247

50 ml Falcon	50 ml RB/OR	30 ml	16 ml	15 ml Falcon	15 ml
					
29 without	29 without	25 708.019	18 708.003	17 708.030	17 708.030
Length in mm	100-120	100	100-105	121	97-120
Adapter Order No.:					




Angle rotor 18 x 1,5/2,0 ml
Angle: 45°




Order No.: 220.95 V06

Ø Tubes in mm
Length in mm
Adapter Order No.:

max. speed: 6000 rpm
RCF-value: 2938 xg
max. radius: 7,3 cm
Acceleration time in s: 11 / 60
Deceleration time in s: 10 / 30

1,5 ml	0,5 ml	0,4/0,2 ml
		
11 without	8 704.005	6 704.004
Length in mm		
Adapter Order No.:		


Swing out rotor 6 x 5 ml
Angle: 0-90°



Order No.: 220.68 V04

Ø Tubes in mm
Length in mm
Adapter Order No.:

max. speed: 4000 rpm
RCF-value: 1896 xg
max. radius: 10,4 cm
Acceleration time in s: 8 / 35
Deceleration time in s: 7 / 25

5 ml

13 75 without
Length in mm
Adapter Order No.:

The Z 206 A accepts up to 12 x 15 ml conical and round bottom tubes.
For tubes with smaller dimensions we offer several adapters.
For larger volumes we offer an angle rotor for 6 x 50 ml conical and round bottom tubes.



Specifications

- Microprocessor with LCD display
- Electrical lid lock
- Pre-selection of the rotor type
- Active imbalance-identification and -cut off
- Manufactured according to international safety regulations
- Noise level under 60 dBA at max. speed
- A large variety of rotors and accessoires
- Easy change of rotors



Distinct Control Panel

- Simple one handed operation
- Easy to program with gloves on
- Foil keyboard
- Permanent indication of preset and actual values
- Selection of speed in both rpm and g-force, with increments of 50/10
- 10 acceleration and deceleration rates
- Pre-selection of the running time from 10 s to 99 h 59 min or continuous

Technical Data

max. speed:	6000 rpm	Dimensions (wxhxd):	28 x 26 x 37 cm
max RCF:	4427 xg	Weight:	15 Kg
max. volume:	6 x 50 ml	Power consumption:	100 W
Speed Range:	200 - 6000 rpm with 50 rpm increments	Order numbers:	
Running time:	59 min 50 s / 10 s increments 99 h 59 min / 1 min increments	306.00 V01 - Z 206 A, 230 V / 50 - 60 Hz	306.00 V02 - Z 206 A, 120 V / 50 - 60 Hz



HERMLE Labortechnik GmbH

Siemensstraße 25 • 78564 Wehingen - Germany

Phone: + 49 7426/9622-11 • Telefax: + 49 7426/9622-49

E-Mail: vertrieb@hermleLT.de • Internet: www.hermle-labortechnik.de

